

Attorney Docket: 042496-0269244
Client Reference: NT-225

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

RECEIVED
CENTRAL FAX CENTER

In re PATENT APPLICATION of: BASOL

Confirmation Number: 4599

AUG 26 2004

Serial No. 09/961,193

Group Art Unit: 1741

Examiner: Edna Wong

Filed: September 20, 2001

Date: August 26, 2004

Title: **Plating Method And Apparatus For Controlling Deposition On Predetermined Portions Of A Workpiece**

CERTIFICATE OF FAX TRANSMISSION
37 C.F.R. §1.8(a)

Fax No. 703-872-9306

I hereby certify that this communication and any attachments are being transmitted via facsimile to the fax number above, addressed to MAIL STOP AMENDMENT, Commissioner for Patents, P. O. Box 1450, Alexandria VA on August 26, 2004


Kathleen M. Smith

RESPONSE TO NOTICE OF NON-COMPLIANT AMENDMENT


Mail Stop Amendments
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

This is a response to the Notice of Non-Compliant Amendment mailed August 16, 2004.
The text of the pending claims with proper status identifiers is attached.

Respectfully submitted,

PILLSBURY WINTHROP LLP


David A. Jakopin, Reg. No. 32995
Tel. No. (650) 233-4790

1. (Previously Presented) A method of plating a conductive top surface of a workpiece, the conductive top surface of the workpiece including a top portion and a cavity portion, the method comprising:

applying, over the conductive top surface of the workpiece, an electrolyte solution with at least one additive disposed therein, a first portion of the additive becoming adsorbed on the top portion and a second portion of the additive becoming adsorbed on the cavity portion;

using a workpiece-surface-influencing device to make physical contact with the top portion and establishing relative movement with the workpiece to change at least the first portion of the additive adsorbed onto the top portion;

moving the workpiece-surface-influencing device away from the workpiece surface so that the physical contact between the workpiece-surface-influencing device and the workpiece no longer occurs; and

plating the conductive top surface of the workpiece with a conductor obtained from the electrolyte solution at least during a period of time when at least some of the change is maintained and while the workpiece-surface-influencing device remains moved away from the workpiece surface, thereby causing greater plating of the cavity portion relative to the top portion.

2. (Original) The method according to claim 1 further including further plating the conductive top surface of the workpiece before and during the steps of using and moving.

3. (Original) The method according to claim 2 wherein the step of using the workpiece-surface-influencing device applies a mask that includes at least one opening therein through which a flow of electrolyte therethrough can be controlled.

4. (Previously Presented) The method according to claim 3 wherein the step of moving the mask away is performed by increasing a pressure of the electrolyte on the mask.

5. (Original) The method according to claim 2 wherein the at least one additive includes a plurality of additives, comprising both a suppressor and an accelerator.

6. (Original) The method according to claim 5 wherein the plurality of additives includes Cl.
7. (Original) The method according to claim 5 wherein, during the step of plating, more effective accelerating additive exists on the cavity portion than on the top portion.
8. (Previously Presented) The method according to claim 7 wherein the step of using the workpiece-surface-influencing device creates the change by at least one of removing accelerator species, activating suppressor species, and increasing suppressor species on the top portion. [[.]]
9. (Previously Presented) The method according to claim 8 wherein the steps of using the workpiece-surface-influencing device, moving the workpiece-surface-influencing device, and plating are repeated.
10. (Previously Presented) The method according to claim 2 wherein the steps of using the workpiece-surface-influencing device, moving the workpiece-surface-influencing device, and plating are repeated.
11. (Original) The method according to claim 2, wherein the step of plating continues without further contact being established between the workpiece-surface-influencing device and the workpiece surface to result in an overfill of the conductor being plated over the cavity portion relative to the top portion of the workpiece surface.
12. (Original) The method according to claim 2 wherein the conductive top surface includes a plurality of cavity portions, and the step of plating plates a conductive layer over the conductive top surface, such that the conductive layer is formed within each of the plurality of cavities, is formed over a flat top surface portion of the conductive top surface with a substantially planar thickness, and is formed over at least one of the plurality of cavity portions with a thickness that is greater than the substantially planar thickness to create an overfill thereover.

13. (Original) The method according to claim 12 wherein the one cavity portion is larger than a plurality of other cavity portions, and the plurality of other cavity portions have formed thereover the thickness of the conductive layer that is greater than the substantially planar thickness to create at least one another overfill thereover, and the one cavity portion has formed thereover the thickness of the conductive layer that is greater than the substantially planar thickness to create the overfill.

14. (Previously Presented) The method according to claim 2 further including the steps, after the step of plating, of:

re-using the workpiece-surface-influencing device to make physical contact with the top portion and establishing relative movement with the workpiece to obtain another change in at least the first portion of the additive adsorbed onto the top portion; again moving the workpiece-surface-influencing device away from the workpiece so that the physical contact between the workpiece surface influencing device and the workpiece no longer occurs; and again plating the conductive top surface of the workpiece with the conductor obtained from the electrolyte solution during another period of time when at least some of the another change is maintained.

15. (Original) The method according to claim 14 wherein the conductive top surface includes a plurality of cavity portions and one cavity portion is larger than a plurality of other cavity portions, and the step of again plating plates a conductive layer over the conductive top surface, such that the conductive layer is formed within each of the plurality of cavities, is formed over a flat top surface portion of the conductive top surface with a substantially planar thickness, is formed over the plurality of other cavity portions with a substantially planar thickness and is formed over at least the one cavity portion with a thickness that is greater than the substantially planar thickness to create an overfill thereover.

16. (Original) The method according to claim 1 wherein the step of plating includes the step of providing at least one of DC, AC and pulsed power during plating.

17. (Original) The method according to claim 16 wherein the step of providing provides DC power and operates, at least part of the time in a current controlled mode in which a plating current is substantially controlled.
18. (Original) The method according to claim 16 wherein the step of providing provides DC power and operates, at least part of the time in a voltage controlled mode in which a plating voltage is substantially controlled.
19. (Previously Presented) The method according to claim 1 wherein the step of plating plates one of copper or a copper alloy.
20. (Previously Presented) The method according to claim 1 wherein power used for plating is not applied during the steps of using and moving.
21. (Original) The method according to claim 1 wherein the step of using the workpiece-surface-influencing device causes a differential in a surface resistance between the top portion and the cavity portion.
22. (Original) The method according to claim 1 further including the step of adding another additive to the electrolyte that assists in loosening a bond between the additive and the surface of the workpiece.
23. (Original) The method according to claim 1 wherein the step of using the workpiece-surface-influencing device uses a sweeper that has a sweeping portion that physically contacts the workpiece with a surface area that is substantially less than the surface area of the workpiece surface.
24. (Previously Presented) The method according to claim 23 wherein the at least one additive includes a plurality of additives, comprising both a suppressor and an accelerator.
25. (Original) The method according to claim 24 wherein, during the step of plating, more effective accelerating additive exists on the cavity portion than on the top portion.

26. (Previously Presented) The method according to claim 25 wherein the step of using the workpiece-surface-influencing device creates the change by one of removing accelerator species and activating suppressor species on the top portion.
27. (Previously Presented) The method according to claim 25 wherein the steps of using the workpiece-surface-influencing device, moving the workpiece-surface-influencing device, and plating are repeated.
28. (Original) The method according to claim 23 wherein the step of using the workpiece-surface-influencing device ensures that the relative movement causes the change over an entire surface area of the workpiece to be plated.
29. (Original) The method according to claim 1 wherein the at least one additive includes a plurality of additives, comprising both a suppressor and an accelerator.
30. (Original) The method according to claim 29 wherein the plurality of additives includes Cl.
31. (Original) The method according to claim 29 wherein, during the step of plating, more effective accelerating additive exists on the cavity portion than on the top portion.
32. (Original) The method according to claim 31 wherein the step of using the workpiece-surface-influencing device creates the change by at least one of removing accelerator species, activating suppressor species, and increasing suppressor species on the top portion.
33. (Previously Presented) The method according to claim 32 wherein the steps of using the workpiece-surface-influencing device, moving the workpiece-surface-influencing device, and plating are repeated.
- 34-72. (Cancelled).

PILLSBURY WINTHROP^{LLP}RECEIVED
CENTRAL FAX CENTER

AUG 26 2004

FACSIMILE

HONG KONG
LONDON
LOS ANGELES
NEW YORK
NORTHERN VIRGINIA
ORANGE COUNTY
PALM BEACH
SACRAMENTO
SAN DIEGO
SAN FRANCISCO
SILICON VALLEY
SINGAPORE
STAMFORD
SYDNEY
TOKYO
WASHINGTON DC

Date: **August 26, 2004**From: **David A. Jakopin**

Phone: 650-233-4790

Total Pages: **7**
(Including cover)

Fax: 650-233-4545

To: **Examiner E. Wong
Group Art Unit 1741**Company: **U.S. Patent & Trademark Office****FAX NO.
703-872-9306**

Serial No. 09/961,193
September 20, 2001
Basol et al.

Confidentiality Note:
The documents accompanying this facsimile transmission may contain confidential information which is legally privileged. The information is intended only for the use of the individual or entity named above. If you are not the intended recipient, or the person responsible for delivering it to the intended recipient, you are hereby notified that any disclosure, copying, distribution or use of any of the information contained in this transmission is strictly PROHIBITED. If you have received this transmission in error, please immediately notify us by telephone and mail the original transmission to us. Thank you.

ATTACHMENTS:**1. Response to Notice of Non-Compliant Amendment**

If you have not properly received this fax, please call . Thank you.
Operator: **Kathleen Smith 650-233-4575**